




P . C . B LAYOUT



CIRCUIT DIAGRAM

NO.	NAME	MATERIAL	QTY	REMARK
1	TERMINAL	C5191	1	Ag plating(0.2μm min)
2	CASE	LCP	1	grey
3	CONTACT	SUS301	1	Ag plating(0.3μm min)
4	DUSTPROOF FILM	PI	1	Yellow
5	COVER	SUS	1	natural color
6	STEM	C2680/PPA	1	Yellow/white

SPECIFICATIONS	
Operating temperature ranges	-30° to +85°
Rating	DC 12V 50mA Max.
Contact Resistance	100mΩ Max
Dielectric strength	250V AC for 1min.
Insulation resistance	100mΩ Min. 100V DC
Travel	0.15±0.05mm
Operating Life(cycles)	100 000 CYCLES

height	model selection
H=1.5mm	
H=1.6mm	
H=1.7mm	
H=2.0mm	
H=2.5mm	
H=3.0mm	

Operating force	model selection
100gf±30gf	
160gf±40gf	
260gf±50gf	

MEASURE POINT:
QUADRANT POINT ☐ QP
TANGENCY POINT ☐ TP
INTERSECTION POINT ☐ IP

UNLESS OTHERWISE
SPECIFIED, TOLERANCE:
X. ±0.25
X.x ±0.20
X.xx ±0.15
X.xxx ±0.10
ANGLES ±2°



深圳金盟实业有限公司
ShenzhenJinmengIndustrialCo., Ltd


TITLE: 轻触开关

4*4*1.5H 铜头贴片

DRAW NO: 01.06.00016

TEL:0755-89973631

THIRD ANGLE PROJECTION



UNIT:

mm

SCALE:

1:1

SIZE:

A4

SHEET:

1/2