







RECOMMENDED PCB LAYOUT(TOP VIEW)T=1.60
DEFAULT TOLERANCE:±0.05



备注:

1. 材质:

1.1 胶芯: LCP+30%G. F. UL94V-0.

1.2 端子: 高导电. T=0.20mm. 半金镍1μ".

1.3 外壳: SUS304, T=0.30mm; 镀镍80μ" Min.

1.4 钢片: SUS301, T=0.15mm;

1.5 护套: PA9T. 黑色.

1.6 环氧树脂: 黑色.

2. 电镀: (具体规格参照客户要求).

2.1 端子: 接触区域镀金&镀锡.

焊接区域镀锡80U" & 镀金G/F.

2.2 外壳: 镀可焊镍50U" MIN.

2.3 盐雾: 24H. (具体规格参照客户要求).

3. 主要特性:

3.1 额定电流: 5.0A.

3.2 接触阻抗: 40 MILLIOHMS Max.

3.3 绝缘阻抗: 150V DC/1000 MΩ.

3.4 耐压测试: 100V AC/ 1 mA Max.

3.5 沾锡性: 温度260±5℃, 时间5±0.5s.

3.6 插入力: 5~20N 2. 拨出力: 8~20N.



耐久: 10000次、拔出力 5~20N.

3.7 工作温度: -55℃~+80℃.

4. 标示"⊙"为零件, 重点检验尺寸.

5. 标示"▼"为FAI尺寸序号.

6. 所有产品符合RoHS环保要求.



MEASURE POINT:
QUADRANT POINT QP
TANGENCY POINT TP
INTERSECTION POINT IP

UNLESS OTHERWISE
SPECIFIED, TOLERANCE:

X. ±0.25

X. x ±0.20

X. xx ±0.15

X. xxx ±0.10

ANGLES ±2°




深圳金盟实业有限公司

ShenzhenJinmengIndustrialCo., Ltd

TITLE:USB C TYPE CONNECTOR

TYPE-C 16P 立插 母座
H=15.00mm (外壳无弹片)

THIRD ANGLE PROJECTION



UNIT:

mm

SCALE:

1:1

SIZE:

A4


SHEET:

1/2


DRAW NO:01.01.00027

TEL:0755-89973631

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND			VBUS	CC1	D+	D-		VBUS			GND
GND			VBUS		D-	D+	CC1	VBUS			GND
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1



COVER示意图



建议防水圈尺寸

MEASURE POINT:
QUADRANT POINT QP
TANGENCY POINT TP
INTERSECTION POINT IP



深圳金盟实业有限公司
ShenzhenJinmengIndustrialCo., Ltd

UNLESS OTHERWISE
SPECIFIED, TOLERANCE:
X. ±0.25
X. x ±0.20
X. xx ±0.15
X. xxx ±0.10
ANGLES ±2°


TITLE:USB C TYPE CONNECTOR

TYPE-C 16P 立插 母座
H=15.00mm (外壳无弹片)

DRAW NO:01.01.00027

TEL:0755-89973631

THIRD ANGLE PROJECTION



UNIT:

mm

SCALE:

1:1

SIZE:

A4

SHEET:

1/2