





3-4: OPERATING TEMPERATURE ; $-40^{\circ} \sim 80^{\circ}$.



 $1/2$

USB TYPE-C PIN ASSIGNMENTS


PIN NUMBER	SIGNAL NAME	PIN NUMBER	SIGNAL NAME
A1	GND	B12	GND
A2	TXp1	B11	RXp1
A3	TXn1	B10	RXn1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	Dp1	B7	Dn2
A7	Dn1	B6	Dp2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	RXn2	B3	TXn2
A11	RXp2	B2	TXp2
A12	GND	B1	GND



Install suction cap diagram

RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED $\pm 0.05\text{mm}$ 

截面B-B



截面A-A

MEASURE POINT:
QUADRANT POINT QP
TANGENCY POINT TP
INTERSECTION POINT IP

UNLESS OTHERWISE
SPECIFIED, TOLERANCE:

X. ± 0.25
X.x ± 0.20
X.xx ± 0.15
X.xxx ± 0.10
ANGLES $\pm 2^\circ$



深圳金盟实业有限公司

ShenzhenJinmengIndustrialCo.,Ltd


TITLE:USB C TYPE CONNECTOR

TYPE-C 16PIN直立式粉末冶金四脚外壳单圈H=7.4 1PX7

DRAW NO:01.01.00036

TEL:0755-89973631

THIRD ANGLE PROJECTION



UNIT:

mm

SCALE:

1:1

SIZE:

A4

SHEET:

1/2